according to Regulation (EC) No. 1907/2006, (REACH).

SDS Reference : 450004N

Varcian : 200 Pevision Date : 01 Apr 15 Print Data : 27 Apr 15



Version : 3.00 Re	Revision Date : 01-Apr-15		Print Date: 27-Apr-15				
Section 1: Identification of t	he substance	/mixture and o	f the company/undertaking				
1.1 Product identifier							
Product code	:	450:004: Shee	n Primer / Finish				
		For colours NOT containing lead chromate pigmentation.					
1.2 Relevant identified uses	of the substa	nce or mixture	and uses advised against				
Use of the Substance/I	Mixture :	See Technica	l Data Sheet.				
		For profession	al use only.				
1.3 Details of the supplier of	f the safety do	ata sheet					
Company	:	Pronto Industr	ial Paints Ltd				
		Stainsby Close					
		Holmewood II Chesterfield	nd. Estate				
		S42 5UG					
Telephone		01246 857777					
Fax	•	01246 857978					
E-Mail	:	info@prontop	aints.co.uk				
1.4 Emergency telephone r	number						
Mon-Fri (08:00-17:00)	:	01246 857777					
Out of office hours	:	07971 494020					

## Section 2: Hazards identification

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008, (CLP)

Flammable Liquids, Category 3	:	H226 Flammable liquid and vapour.
Skin Irritation, Category 2	:	H315 Causes skin irritation.
Chronic Aquatic Toxicity, Category 2	:	H411 Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

## Labelling according to Regulation (EC) No. 1272/2008, (CLP)

:

Hazard pictograms

Signal word	: Warning
Hazard statements	: H226 Flammable liquid and vapour.
	H315 Causes skin irritation.
	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	: P210 Keep away from heat, hot surfaces, sparks, open

according to Regulation (EC) No. 1907/2006, (REACH).

SDS Reference : 450004N

Version: 3.00

Revision Date : 01-Apr-15 Print Date : 27-Apr-15



flames and other ignition sources. No smoking. P273 Avoid release to the environment. P280 Wear protective gloves, protective clothing, eye protection and face protection. P321 Specific treatment (see FIRST AID measures on this label). P370+P378 In case of fire: Use alcohol-resistant foam to extinguish. P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental hazard information : None.

## 2.3 Other hazards

### Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

### Section 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable.

#### 3.2 Mixtures

Description of the mixture : Mixture of resins, solvents, pigments and additives.

#### Hazardous components

Chemical name	EC	CAS	REACH	%	Classification
	Number	Number	Registration	[weight]	[Regulation
			Number		(EC) No.
					1272/2008]
xylene	215-535-7	1330-20-7		25%-50%	H226, H312, H315, H332
hydrocarbons, c9, aromatics	918-668-5		01-2119455851-35	10%-25%	H226, H304, H335, H336, H411, EUH066
trizinc bis(orthophosphate)	231-944-3	7779-90-0	01-2119485044-40	2.5%-10%	H400, H410
ethylbenzene	202-849-4	100-41-4		<6.2%	H225, H332
n-butyl acetate	204-658-1	123-86-4		1.0%-2.5%	H226, H336, EUH066
2-methoxy-1-methylethyl acetate	203-603-9	108-65-6		0.1%-1.0%	H226
solvent naphtha (petroleum), light aromatic	265-199-0	64742-95-6		0.1%-1.0%	H304
zinc oxide	215-222-5	1314-13-2	01-2119463881-32	0.1%-1.0%	H400, H410

according to Regulation (EC) No. 1907/2006, (REACH).

## SDS Reference : 450004N

Version: 3.00

Revision Date : 01-Apr-15

Print Date: 27-Apr-15



1,2,4-trimethylbenzene	202-436-9	95-63-6	0.1%-1.0%	H226, H315,
				H319, H332,
				H335, H411

### Additional information :

For the full text of the Hazard Statements mentioned in this Section, see Section 16.

Section 4: First aid measures						
4.1 Description of first aid measures						
General notes		In all cases of doubt, or when symptoms persist, seek medical attention.				
		Never give anything by mouth to an unconscious person.				
		If unconscious place in recovery position and seek medical advice.				
If inhaled	:	Remove to fresh air, keep patient warm and at rest.				
		If breathing is irregular or stopped, administer artificial respiration.				
In case of skin contact	:	Remove contaminated clothing.				
		Wash skin thoroughly with soap and water or use recognised skin cleanser.				
		Do NOT use solvents or thinners.				
In case of eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.				
If swallowed	:	If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.				
		Keep at rest.				
		Do NOT induce vomiting.				
Self-protection of the first aider	:	None.				
4.2 Most important symptoms and eff	iects	, both acute and delayed				
	:	None.				
4.3 Indication of any immediate med	lical	attention and special treatment needed				
	:	None.				
Section 5: Firefighting measures						
5.1 Extinguishing media						
Suitable extinguishing media	:	Alcohol resistant foam, CO2, powders and water spray/mist.				
Unsuitable extinguishing media	:	Water jet.				
5.2 Special hazards arising from the s	ubst	ance or mixture				
		Page 3 of 11				
		Page 3 of 11				

SDS Reference : <b>450004N</b>	
Version : 3.00 Revision	n Date : 01-Apr-15 Print Date : 27-Apr-15
Hazardous combustion prod	ucts : Fire will produce dense black smoke.
	Exposure to decomposition products may cause a health hazard.
	Appropriate breathing apparatus may be required.
5.3 Advice for firefighters	: Cool closed containers exposed to fire with water.
	Do not allow run-off from fire fighting to enter drains or watercourses.
Section 6: Accidental release me	asures
6.1 Personal precautions, protect	ive equipment and emergency procedures
	: Exclude sources of ignition and ventilate the area.
	Avoid breathing vapours.
	Refer to protective measures listed in Sections 7 and 8.
6.2 Environmental precautions	: Do not allow to enter drains or watercourses.
	If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.
6.3 Methods and material for cor	tainment and cleaning up
	: Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see Section 13).
	Clean preferably with a detergent - avoid use of solvents.
6.4 Reference to other Sections	: None.
Section 7: Handling and storage	
7.1 Precautions for safe handling	
Advice on safe handling	: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
	In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
	Electrical equipment should be protected to the appropriate standard.
	Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.
	Operators should wear anti-static footwear and clothing and floors should be of the conducting type.

according to Regulation (EC) No. 1907/2006, (REACH).

Revision Date : 01-Apr-15

SDS Reference : 450004N

Version: 3.00



-			
			Isolate from sources of heat, sparks and open flame.
			No sparking tools should be used.
			Avoid skin and eye contact.
			Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture.
			Avoid inhalation of dust from sanding.
			Smoking, eating and drinking should be prohibited in application area.
			For personal protection see Section 8.
			Never use pressure to empty: container is not a pressure vessel.
			Always keep in containers of same material as the original one.
			Comply with the health and safety at work laws.
			Do not allow to enter drains or watercourses.
	Advice on protection against	:	Vapours are heavier than air and may spread along floors.
	fire and explosion		Vapours may form explosive mixtures with air.
7.2	Conditions for safe storage, including	ŋg	any incompatibilities
	Requirements for storage areas and containers	:	Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.
	Notes on joint storage	:	Store away from oxidising agents, from strongly alkaline and strongly acid materials.
	Additional information on	:	Observe label precautions.
	storage conditions		Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat and direct sunlight.
			Keep container tightly closed.
			Keep away from sources of ignition.
			No smoking.
			Prevent unauthorised access.
			Containers which are opened must be carefully resealed and kept upright to prevent leakage.
			The principles contained in the HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product.
7.3	Specific end use(s)	:	None.

according to Regulation (EC) No. 1907/2006, (REACH).

SDS Reference : 450004N

Version: 3.00 Revision Date : 01-Apr-15 Print Date: 27-Apr-15



### Section 8: Exposure controls/personal protection

#### 8.1 Control parameters

Limits for occupational exposure and/or biological limit values.

Chemical name Physical state		LTEL - 8	hr TWA	STEL -	Notes	
		ppm	mg/m³	ppm	mg/m³	
xylene		50	220	100	441	Sk, BMGV
ethylbenzene		100	441	125	552	Sk
n-butyl acetate		150	724	200	966	
2-methoxy-1-methylethyl acetate		50	274	100	548	Sk

LTEL - Long Term Exposure Limit, STEL - Short Term Exposure Limit, TWA - Time-Weighted Average.

ppm - parts per million by volume, mg/m<sup>3</sup> - milligrams per cubic metre.

BMGV - Biological Monitoring Guidance Values are given in Table 2 of EH40/2005 Workplace exposure limits.

Carc - Capable of causing cancer and/or heritable genetic damage.

Sen - Capable of causing occupational asthma.

Sk - Can be absorbed through the skin. Dermal absorption may lead to systemic toxicity.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

General advice : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particules and solvent vapour below the OEL, suitable respiratory protection must be worn. 8.2.2 Personal protection equipment Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Hand protection : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged or repeated handling, use Polyvinyl Alcohol (PVA) or Viton Rubber (FluorRubber). The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

according to Regulation (EC) No. 1907/2006, (REACH).

### SDS Reference : 450004N

Version: 3.00 Revision Date : 01-Apr-15



		Always ensure that gloves are free from defects and that they are stored and used correctly.
		The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
		Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occured.
Eye protection	:	Use safety eyewear designed to protect against splash of liquids.
Skin protection	:	Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.
8.2.3 Environmental exposure controls		
		De not allow to optor drains or wateroouson

: Do not allow to enter drains or watercouses.

## Section 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Appearance - Physical state	:	Viscous liquid.
- Colour	:	Various.
Odour	:	Aromatic hydrocarbons. Slight fruity.
Odour threshold - Lower	:	Not determined.
- Higher	:	Not determined.
рН	:	Not determined.
Melting point/freezing point (°C)	:	Not determined.
Initial boiling point and boiling range (°C)	:	126-200
Flash point (°C)	:	27
Evaporation rate	:	>0.77 (BuAc=1)
Flammability/explosive limits - Lower (%)	:	Not determined.
- Higher (%	):	Not determined.
Vapour pressure	:	Not determined.
Vapour density (air=1)	:	Heavier than air.
Relative density (g/ml)	:	1.05-1.27
Solubility(ies)	:	Miscible with organic solvents.
Partition coefficient	:	Not determined.
Auto-ignition temperature (°C)	:	>400
Decomposition temperature (°C)	:	Not determined.
Viscosity	:	~3.0 poise.
Explosive properties	:	May form explosive mixtures with air.

according to Regulation (EC) No. 1907/2006, (REACH).

## SDS Reference : 450004N

Version : 3.00 Revision Date : 01-Apr-15

Print Date: 27-Apr-15



Oxidising properties	: Not determined.
9.2 Other information	
None.	
Section 10: Stability and reactivity	
10.1 Reactivity	: No data available.
10.2 Chemical stability	: Stable under recommended storage and handling conditions. (See Section 7).
10.3 Possibility of hazardous reactions	: Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: No data available.
10.6 Hazardous decomposition products	: Carbon monoxide and dioxide, smoke, oxides of nitrogen.

### Section 11: Toxicological information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Classification, Labelling and Packaging of Substances and Mixtures Regulation (EC) No. 1272/2008, (CLP) and classified for toxicological hazards accordingly.

See Sections 2 and 3 for details.

### 11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhoea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Section 12: Ecological information

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

according to Regulation (EC) No. 1907/2006, (REACH).

#### SDS Reference : 450004N

Version : 3.00 Revision Date : 01-Apr-15

Print Date: 27-Apr-15



12.1 Toxicity	: No data available.	
12.2 Persistence and degradability	: No data available.	
12.3 Bioaccumulative potential	: No data available.	
12.4 Mobility in soil	: No data available.	
12.5 Results of PBT and vPvB assessment	: No data available.	
12.6 Other adverse effects	: No data available.	

#### Section 13: Disposal considerations

#### 13.1 Waste treatment methods

Do not allow to enter drains or watercourses.

The European List of Waste classification of this product, when disposed of as waste, is

Waste Code:	Name of Waste (according to Commission Decision 2000/532/EC):
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

### Section 14: Transport information

## 14.1 UN number

	ADR/RID/ADN	:	1263
	IMDG	:	1263
	ICAO	:	1263
14.	2 UN proper shipping name	:	PAINT
14.	3 Transport hazard class(es)		
	ADR/RID/ADN Class	:	3
	ADR/RID/ADN Class	:	Class 3: Flammable liquids.
	ADR Label number	:	3
	IMDG Class	:	3
	ICAO Class/Division	:	3


according to Regulation (EC) No. 1907/2006, (REACH).

### SDS Reference : 450004N

Version: 3.00 Revision Date: 01-Apr-15



Transport labels



Print Date: 27-Apr-15

## 14.4 Packing group

ADR/RID/ADN	: 111
IMDG	: 111
ICAO	: 111
14.5 Environmental hazards	: Environmentally Hazardous Substance/Marine Pollutant.
14.6 Special precautions for user	
ADR Tunnel Restriction Code	: (D/E)
IMDG EmS	: F-E, S-E
IMDG Stowage Category	: A

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an acident or spillage.

## 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable. :

## Section 15: Regulatory information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The information in this Safety Data Sheet is required pursuant to :

- Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No. 1907/2006, (REACH).
- Classification, Labelling and Packaging of substances and mixtures, Regulation (EC) No. 1272/2008, (CLP).
- The Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR).
- The Control of Substances Hazardous to Health Regulations, 2002, (COSHH).
- The Health and Safety at Work etc Act, 1974, (HSWA).

Approved Codes of Practice and Guidance notes relevant to this Safety Data Sheet :

- The European Chemicals Agency (ECHA) Guidance on the compilation of safety data sheets, Version 2.1.
- CEPE Guideline for Safety Data Sheets, 9th Edition.
- HSE Approved Code of Practice and Guidance, Dangerous Substances and Explosive Atmospheres.
- HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances.
- HSE publication, EH40/2005 Workplace exposure limits.

according to Regulation (EC) No. 1907/2006, (REACH).

SDS Reference : 450004N

Version : 3.00 Revision Date : 01-Apr-15

### Print Date: 27-Apr-15



### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### Section 16: Other information

#### Full text of Hazard Statements referred to in Section 3.

- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H304 : May be fatal if swallowed and enters airways.
- H312 : Harmful in contact with skin.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H400 : Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### **Revision history**

Revision date	:	01-Apr-15
Version	:	3.00
Sections updated	:	Format and all sections updated for CLP/REACH regulation changes.
Supercedes date	:	30-Aug-07
Supercedes version	:	2.12

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown on the Technical Data Sheet without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this Safety Data Sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.