

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** ProXL® PLASTIGRIP 500 ML
- **Article number:** PLASTIGRIP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Preparation
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
ProXL
Second Avenue
Chatham
Kent
ME4 5AU
Tel: +44 (0)1634 823900
Fax: +44 (0)1634 823909
Email: info@pro-xl.co.uk
- **Further information obtainable from:** QHSE Department
- **1.4 Emergency telephone number:**
Tel: +44(0) 1634 823900 (08.00 / 17.00)

+31 629058130 (24 h/d, 7 d/wk)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R38: Irritating to skin.



F+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 1)

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31















Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 2)

· Dangerous components:		
CAS: 64742-49-0 EC number: 921-024-6 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35-xxxx	Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)  Xn R65  Xi R38  F R11  N R51/53 R67 -----  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	50-75%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  F+ R12 -----  Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas C, H280	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene  Xn R20/21  Xi R38 R10 -----  Flam. Liq. 3, H226  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-10%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 3)

- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm
Sk; BMGV	

- **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:** Not required.

(Contd. on page 5)

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 4)

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Not required.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Not applicable, as aerosol.

· **Flash point:** < 0 °C (< 32 °F)
Not applicable, as aerosol.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** > 200 °C (> 392 °F)

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

· **Explosion limits:**

· Lower:	0.6 Vol %
· Upper:	26.2 Vol %

· **Vapour pressure at 20 °C (68 °F):** 4000 hPa (3000 mm Hg)

· **Density at 20 °C (68 °F):** 0.707 g/cm³ (5.9 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 5)

- | | |
|---|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 99.1 % |
| · EU-VOC: | 700.4 g/l |
| · EU-VOC in %: | 99.07 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m ³ (rat)

115-10-6 dimethyl ether

Inhalative	LC50 / 4 h	308 mg/m ³ (rat)
------------	------------	-----------------------------

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	22.1 mg/m ³ (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

64742-49-0 Naphtha (petroleum), hydrotreated light (< 0,1 % benzol CAS nr. 71-43-2)

LC50	127-159 mg/l (Leuciscus idus)
------	-------------------------------

115-10-6 dimethyl ether

EC50 / 48 h	>4000 mg/l (daphnia magna)
-------------	----------------------------

1330-20-7 xylene

EC50 / 48 h	7.4 mg/l (daphnia magna)
-------------	--------------------------

LC50 / 96 h	13.5 mg/l (fish)
-------------	------------------

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

20 01 13*	solvents
-----------	----------

15 01 04	metallic packaging
----------	--------------------

Uncleaned packaging:

Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.
· Label 2.1

· IMDG, IATA



· Class 2.1
· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Gases.

· Danger code (Kemler):

-

· EMS Number:

F-D,S-U

· 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

IL

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

IL

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation":

UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

* **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 03.12.2014

Version number 37

Revision: 24.11.2014

Trade name: ProXL® PRO PLASTI GRIP 500 ML

(Contd. of page 8)

· **Relevant phrases**

- H220 *Extremely flammable gas.*
- H224 *Extremely flammable liquid and vapour.*
- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H280 *Contains gas under pressure; may explode if heated.*
- H304 *May be fatal if swallowed and enters airways.*
- H312 *Harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H332 *Harmful if inhaled.*
- H336 *May cause drowsiness or dizziness.*
- H411 *Toxic to aquatic life with long lasting effects.*
- R10 *Flammable.*
- R11 *Highly flammable.*
- R12 *Extremely flammable.*
- R20/21 *Harmful by inhalation and in contact with skin.*
- R38 *Irritating to skin.*
- R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- R65 *Harmful: may cause lung damage if swallowed.*
- R67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS:** R&D legislation and regulatory advisor

· **Contact:** QHSE Department

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas C: Gases under pressure: Compressed gas
- Flam. Liq. 1: Flammable liquids, Hazard Category 1
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· *** Data compared to the previous version altered.**

GB