

ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Compilation date: 20/02/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Product code: ATCS400

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

1.4. Emergency telephone number

Emergency tel: 01753 584500

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Flam. Aerosol 1: H222; STOT SE 3: H336; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



SAFETY DATA SHEET

ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 2

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251: Do not pierce or burn, even after use.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405: Store locked up.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501: Dispose of contents/container to in accordance with with local regulations.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/VPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIMETHYL ETHER

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|--|-------------------------------------|---------|
| 204-065-8 | 115-10-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 50-70% |

ACETONE

| | | | | |
|-----------|---------|---|--|--------|
| 200-662-2 | 67-64-1 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066 | 30-50% |
|-----------|---------|---|--|--------|

XYLENE

| | | | | |
|-----------|-----------|---|---|-------|
| 215-535-7 | 1330-20-7 | - | Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315 | 1-10% |
|-----------|-----------|---|---|-------|

N-BUTYL ACETATE

| | | | | |
|-----------|----------|--|--|-------|
| 204-658-1 | 123-86-4 | Substance with a Community workplace exposure limit. | Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066 | 1-10% |
|-----------|----------|--|--|-------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

SAFETY DATA SHEET

ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.
Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIMETHYL ETHER

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|-----------------------|-----------------------|------------|--------------|
| UK | 766 mg/m ³ | 958 mg/m ³ | - | - |

ACETONE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1210 mg/m ³ | 3620 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

XYLENE

| | | | | |
|----|-----------------------|-----------------------|---|---|
| UK | 220 mg/m ³ | 441 mg/m ³ | - | - |
|----|-----------------------|-----------------------|---|---|

N-BUTYL ACETATE

| | | | | |
|----|-----------------------|-----------------------|---|---|
| UK | 724 mg/m ³ | 966 mg/m ³ | - | - |
|----|-----------------------|-----------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

[cont...]

SAFETY DATA SHEET

.P-ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Various

Odour: Characteristic odour

Solubility in water: Not miscible

Viscosity: Non-viscous

Boiling point/range°C: Not applicable.

Melting point/range°C: No data available.

Flammability limits %: lower: 2.6

upper: 18.6

Flash point°C: Not applicable.

Vapour pressure: 4000

Relative density: 0.719

VOC g/l: 719

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

.P-ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 6

ACETONE

| | | | | |
|-----|-----|------|------|-------|
| IVN | RAT | LD50 | 5500 | mg/kg |
| ORL | MUS | LD50 | 3000 | mg/kg |
| ORL | RAT | LD50 | 5800 | mg/kg |

XYLENE

| | | | | |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 2119 | mg/kg |
| ORL | RAT | LD50 | 4300 | mg/kg |
| SCU | RAT | LD50 | 1700 | mg/kg |

N-BUTYL ACETATE

| | | | | |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 6 | gm/kg |
| ORL | RAT | LD50 | 10768 | mg/kg |

Relevant hazards for substance:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

| | | | |
|---|------|------|------|
| BLUEGILL (<i>Lepomis macrochirus</i>) | LC50 | 8300 | mg/l |
|---|------|------|------|

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

[cont...]

SAFETY DATA SHEET

.P-ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 7

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

14.3. Transport hazard class: 2.1

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

[cont...]

SAFETY DATA SHEET

.P-ATCS400 CUSTOM FILLED SPECIAL AEROSOL

Page: 8

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.