

EP135 2PK CHROMATE FREE ETCH PRIMER

Compilation date: 26/11/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EP135 2PK CHROMATE FREE ETCH PRIMER

Product code: EP135

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited
Unit 4 Transcentral
Bennet Road
Reading
RG2 0QX
Great Britain
Tel: 01753 584500
Fax: 01753 584501
Email: sales@unovaproducts.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Emergency tel: 01753 584500

Classification under CLP: Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336; Flam. Liq. 2: H225; Acute Tox. 4: H302

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Harmful if swallowed.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.
H302: Harmful if swallowed.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark
GHS02: Flame

SAFETY DATA SHEET

EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 2



Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical equipment.

P261: Avoid breathing vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL METHYL KETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%
-----------	-----------	---	--	--------

ISOBUTANOL

201-148-0	78-83-1	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	10-30%
-----------	---------	---	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

[cont...]

SAFETY DATA SHEET

EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

.P-EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 4

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL METHYL KETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600 mg/m ³	899 mg/m ³	-	-

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

ISOBUTANOL

UK	154 mg/m ³	231 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: No data available.

Solubility in water: Not miscible

[cont...]

SAFETY DATA SHEET

.P-EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 5

Viscosity: Non-viscous

Boiling point/range°C: 137-141

Flammability limits %: lower: No data available.

Flash point°C: No data available.

Autoflammability°C: No data available.

Relative density: 1.2

VOC g/l: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: 7.0 Hg @20 c

pH: No data available.

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Other information: No data available.

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

10.3. Possibility of hazardous reactions

Chemical stability: Stable under normal conditions.

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

[cont...]

SAFETY DATA SHEET

.P-EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 6

ISOBUTANOL

IVN	MUS	LD50	417	mg/kg
IVN	RAT	LD50	340	mg/kg
ORL	RAT	LD50	2460	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Ecotoxicity values: No data available.

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

Bioaccumulative potential: No bioaccumulation potential.

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

PBT identification: This product is not identified as a PBT/vPvB substance.

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

.P-EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 7

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Shipping name: PAINT OR PAINT RELATED MATERIAL

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Packing group: III

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special precautions: No special precautions.

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

[cont...]

SAFETY DATA SHEET

.P-EP135 2PK CHROMATE FREE ETCH PRIMER

Page: 8

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.