

HA405 ACTIVATOR

MATERIAL SAFETY DATA SHEET

Compilation date: 29/04/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HA405 ACTIVATOR

Product code: HA405

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited

Unit 4 Transcentral Bennet Road Reading RG2 0QX Great Britain

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

1.4. Emergency telephone number

Emergency tel: 01753 584500

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH208

Most important adverse effects: Contains toluene-2,4-di-isocyanate. May produce an allergic reaction. Highly flammable

liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains toluene-2,4-di-isocyanate. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



HA405 ACTIVATOR

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336;	50-70%
			-: EUH066	

TOLUENE DIISOCYANATE POLYMER

-	9017-01-0	-	Eye Irrit. 2: H319; Skin Sens. 1: H317;	10-30%
			Acute Tox. 4: H332	

HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

-	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332;	10-30%
			Skin Sens. 1: H317	

ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	10-30%
			STOT SE 3: H336; -: EUH066	

TOLUENE-2,4-DI-ISOCYANATE

209-544-5	584-84-9	-	Carc. 2: H351; Acute Tox. 2: H330; Eye	<1%
			Irrit. 2: H319; STOT SE 3: H335; Skin	
			Irrit. 2: H315; Resp. Sens. 1: H334;	
			Skin Sens. 1: H317; Aquatic Chronic 3:	
			H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

HA405 ACTIVATOR

Page: 3

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

HA405 ACTIVATOR

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:					
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
	UK	724 mg/m3	966 mg/m3	-	-

ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Hand protection: Protective gloves. Eye protection: Safety glasses. Ensure eye bath is to hand. Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- State: Liquid
- Colour: Colourless
- Odour: Characteristic odour
- Evaporation rate: No data available.
 - Oxidising: Non-oxidising (by EC criteria)
- Solubility in water: No data available.
 - Viscosity: Non-viscous

HA405 ACTIVATOR

Kinematic viscosity:	0.205		-
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/31 05)		
Boiling point/range°C:	78	Melting point/range°C:	No data available.
Flammability limits %: lower:	1.38	upper:	10
Flash point°C:	7	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	1.6
Relative density:	0.95	pH:	No data available.
VOC g/l:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

HA405 ACTIVATOR

HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

GASES	RAT	4H LC50	390-453	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

HA405 ACTIVATOR

		Page:	7
Section 14: Transport informat	ion		
14.1. UN number			
	1014022		
UN number:	UN1263		
14.2. UN proper shipping name			
Shipping name:	PAINT		
14.3. Transport hazard class(es			
Transport class:	3		
14.4. Packing group			
Packing group:	2		
14.5. Environmental hazards			
Environmentally hazardous:	No Marine pollutant: No		
14.6. Special precautions for us	-		
Special precautions: Tunnel code:	No special precautions.		
Transport category:			
Section 15: Regulatory informa			
Section 15. Regulatory morna			
15.1. Safety, health and environ	mental regulations/legislation specific for the substance or mixture		
Specific regulations:	Not applicable.		
15.2. Chemical Safety Assessm	ent		
 Section 16: Other information			
 Other information			
Other information			
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No		
	453/2010.		
	* indicates text in the SDS which has changed since the last revision.		
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.		
	EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name>		
	H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour.		
	H315: Causes skin irritation.		
	H317: May cause an allergic skin reaction.		
	H319: Causes serious eye irritation.		
	H330: Fatal if inhaled.		
	H332: Harmful if inhaled.		
	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.		

HA405 ACTIVATOR

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven

that no other routes of exposure cause the hazard>.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.