

# MATERIAL SAFETY DATA SHEET

Compilation date: 15/09/2015

Revision No: 1

# **HA406 ACTIVATOR**

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: HA406 ACTIVATOR

Product code: HA406

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

**Great Britain** 

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

## 1.4. Emergency telephone number

Emergency tel: 01753 584500

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Acute Tox. 4: H312+332; Flam. Liq. 2: H225; Eye Irrit. 2: H319; Skin

Irrit. 2: H315; Skin Sens. 1: H317; -: EUH066; -: EUH208

Most important adverse effects: Highly flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes

skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Repeated exposure may cause skin dryness or cracking.

Contains hexamethylene-di-isocyanate. May produce an allergic reaction.

#### 2.2. Label elements

#### Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains hexamethylene-di-isocyanate. May produce an allergic reaction.

[cont...]

## HA406 ACTIVATOR

Page: 2

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P312: Call a POISON CENTER/doctor/physician/if you feel unwell.

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information oningredients

## 3.2. Mixtures

## **Hazardous ingredients:**

## **XYLENE**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	30-50%
1-METHOXY-2	2-PROPANOL			
203-539-1	107-98-2	-	Flam. Liq. 3: H226; STOT SE 3: H336	10-30%
HOMOPOLYM	ER OF HEXAME	THYLENE DIISOCYANATE		
-	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	10-30%
2-METHOXY-1	-METHYLETHYL	ACETATE		
203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
ETHYLBENZE	NE			
202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%

.P-HA406 ACTIVATOR

Page: 3

#### HEXAMETHYLENE-DI-ISOCYANATE

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319;	<1%
			STOT SE 3: H335; Skin Irrit. 2: H315;	
			Resp. Sens. 1: H334; Skin Sens. 1:	
			H317	

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from

the stomach may cause symptoms similar to direct inhalation.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness

or mental confusion may occur.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

.P-HA406 ACTIVATOR

Page: 4

downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. If outside keep bystanders upwind and away from danger point.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

## 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## Hazardous ingredients:

# XYLENE

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
UK	220 mg/m3	441 mg/m3	-	-	
1-METHOXY-2-PROPANOL					
UK	375 mg/m3	560 mg/m3	-	-	

# 2-METHOXY-1-METHYLETHYL ACETATE

UK   2/4 mg/m3   548 mg/m3   -	UK	274 mg/m3	548 mg/m3	-	
--------------------------------	----	-----------	-----------	---	--

## **ETHYLBENZENE**

UK	441 mg/m3	552 mg/m3	-	-

.P-HA406 ACTIVATOR

Page: 5

#### **N-BUTYL ACETATE**

UK	724 mg/m3	966 mg/m3	-	-		
HEXAMETHYLENE-DI-ISOCYANATE						
UK	0.02 mg/m3	0.07 mg/m3	-	-		

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

**Evaporation rate:** Slow

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: No data available.

Boiling point/range°C: >35 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point C: <23 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.914 pH: No data available.

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

.P-HA406 ACTIVATOR

Page: 6

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

## **Hazardous ingredients:**

#### **XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

#### 1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

## HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

GASES	RAT	4H LC50	390-453	mg/l
ORAL	RAT	LD50	>5000	mg/kg

## 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

## **ETHYLBENZENE**

IPR	MUS	LD50	2624	μl/kg
ORL	RAT	LD50	3500	mg/kg

.P-HA406 ACTIVATOR

Page: 7

#### **N-BUTYL ACETATE**

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### **HEXAMETHYLENE-DI-ISOCYANATE**

IVN	MUS	LD50	5600	μg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	μl/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

## Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from

the stomach may cause symptoms similar to direct inhalation.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness

or mental confusion may occur.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

## 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

.P-HA406 ACTIVATOR

Page: 8

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1263

## 14.2. UN proper shipping name

Shipping name: PAINT OR PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: ||

#### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

#### 14.6. Special precautions for user

Special precautions: No special precautions.

# Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

## 15.2. Chemical Safety Assessment

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

#### .P-HA406 ACTIVATOR

Page: 9

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.