

MATERIAL SAFETY DATA SHEET

Compilation date: 29/04/2015

Revision No: 1

HA408 ACTIVATOR

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HA408 ACTIVATOR

Product code: HA408

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

1.4. Emergency telephone number

Emergency tel: 01753 584500

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Acute Tox. 4: H332; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin

Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause

allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory

irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

Signal words: Danger

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard

HA408 ACTIVATOR



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing.

P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	30-50%
XYLENE	·			
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	30-50%
N-BUTYL ACE	TATE			
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
2-METHOXY-1	-METHYLETHYL	ACETATE		
203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
4-ISOCYANAT	OSULPHONYLT	OLUENE		
223-810-8	4083-64-1	-	Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; -: EUH014	<1%
DIBUTILSTAG	NO DILAURATO	(A)		
201-039-8	77-58-7	-	Acute Tox. 3: H301; Acute Tox. 4: H312; Acute Tox. 4: H332	<1%

Page: 2

HA408 ACTIVATOR

Page: 3

P-TOLUENESULPHONYLCHLORIDE

202-684-8	98-59-9	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	<1%	l
-----------	---------	---	---	-----	---

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, give

half a litre of water to drink immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from

the stomach may cause symptoms similar to direct inhalation.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the throat with a

feeling of tightness in the chest. Drowsiness or mental confusion may occur.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point.

HA408 ACTIVATOR

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	•	•

N-BUTYL ACETATE

UK	724 mg/m3	966 mg/m3	-	-
	•	<u> </u>		

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m3	548 mg/m3	-	-
----	-----------	-----------	---	---

4-ISOCYANATOSULPHONYLTOLUENE

UK	0.02 mg/m^2			
UN	0.02 mg/m3	0.07 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

HA408 ACTIVATOR

Page: 5

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Sweet-smelling

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: No data available.

Viscosity: No data available.

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.967 pH: No data available.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

HA408 ACTIVATOR

Page: 6

Hazardous ingredients:

HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE

GASES	RAT	4H LC50	390-453	mg/l
ORAL	RAT	LD50	>5000	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

4-ISOCYANATOSULPHONYLTOLUENE

IPR	RAT	LD50	775	mg/kg
ORL	RAT	LD50	2234	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from

the stomach may cause symptoms similar to direct inhalation.

Inhalation: Exposure may cause coughing or wheezing. There may be irritation of the throat with a

feeling of tightness in the chest. Drowsiness or mental confusion may occur.

Section 12: Ecological information

HA408 ACTIVATOR

Page: 7

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 3

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 1

HA408 ACTIVATOR

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH014: Reacts violently with water.

EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.