



# **MO145 MICACEOUS IRON OXIDE PRIMER**

Compilation date: 07/05/2015

Revision No: 1

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: MO145 MICACEOUS IRON OXIDE PRIMER

Product code: MO145

1.2. Relevant identified uses of the substance or mixture and uses advised against

## **1.3. Details of the supplier of the safety data sheet**

Company name: Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

## 1.4. Emergency telephone number

Emergency tel: 01753 584500

# Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Asp. Tox. 1: H304; Acute Tox. 4: H332; Skin Irrit. 2: H315; Eye Irrit. 2:

H319

#### Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful if

inhaled. Causes skin irritation. Causes serious eye irritation.

#### 2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H332: Harmful if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



#### MO145 MICACEOUS IRON OXIDE PRIMER

	<b>Page:</b> 2
Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition	
sources. No smoking.	
P233: Keep container tightly closed.	
P280: Wear protective gloves/protective clothing/eye protection/face protection.	
P403+235: Store in a well-ventilated place. Keep cool.	
P261: Avoid breathing vapours.	

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

#### Hazardous ingredients:

#### XYLENE

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
2	215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	30-50%

## Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### MO145 MICACEOUS IRON OXIDE PRIMER

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

#### Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

## MO145 MICACEOUS IRON OXIDE PRIMER

Page: 4

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## Hazardous ingredients:

## XYLENE

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m3	441 mg/m3	-	-

**Respirable dust** 

#### **DNEL/PNEC Values**

DNEL / PNEC No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Various		
Odour:	Characteristic odour		
Evaporation rate:	No data available.		
Oxidising:	No data available.		
Solubility in water:	Notmiscible		
Boiling point/range°C:	140	Flammability limits %: lower:	1.0
upper:	7	Flash point°C:	25
Part.coeff. n-octanol/water:	No data available.	Autoflammability°C:	465
Vapour pressure:	7.0	Relative density:	1.1
pH:	No data available.		

#### 9.2. Other information

Other information: No data available.

#### MO145 MICACEOUS IRON OXIDE PRIMER

Page: 5

#### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

## 11.1. Information on toxicological effects

#### Hazardous ingredients:

## XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

## Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

## MO145 MICACEOUS IRON OXIDE PRIMER

**Page:** 6

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## Section 14: Transport information

14.1. UN number

UN number: UN1263

#### 14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 3

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## MO145 MICACEOUS IRON OXIDE PRIMER

Page: 7

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 1

## Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

## Section 16: Other information

# Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	453/2010.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H226: Flammable liquid and vapour.	
	H304: May be fatal if swallowed and enters airways.	
	H312: Harmful in contact with skin.	
	H315: Causes skin irritation.	
	H319: Causes serious eye irritation.	
	H332: Harmful if inhaled.	
Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	