

PR229 WATERBORNE PRIMER

MATERIAL SAFETY DATA SHEET

Compilation date: 07/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PR229 WATERBORNE PRIMER

Product code: PR229

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

Tel: 01753 584500

Fax: 01753 584501

Email: sales@unovaproducts.com

1.4. Emergency telephone number

Emergency tel: 01753 584500

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412

Most important adverse effects: Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H412: Harmful to aquatic life with long lasting effects.

Precautionary statements: P273: Avoid release to the environment.

P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

PR229 WATERBORNE PRIMER

Page: 2

Hazardous ingredients:

2-BUTOXYETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%

ZINC OXIDE

-	1314-13-2	-	Aquatic Chronic 1: H410; Aquatic Acute	1-10%	
			1: H400		I

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

PR229 WATERBORNE PRIMER

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-BUTOXYETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

ZINC OXIDE

UK 5 mg/m3 10 mg/m3	
---------------------	--

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

- Eye protection: Safety glasses.
- Skin protection: Protective clothing.

Page: 3

PR229 WATERBORNE PRIMER

Page: 4

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties					
State:	Liquid				
Colour:	White				
Odour:	Characteristic odour				
Evaporation rate:	Slow				
Oxidising:	Non-oxidising (by EC criteria)				
Solubility in water:	Soluble				
Kinematic viscosity:	>0.205				
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C (ISC	3104/31 05)			
Boiling point/range°C:	100	Melting point/range°C:	No data available.		
Flammability limits %: lower:	1.1	upper:	12.5		
Flash point°C:	93.3 P	Part.coeff. n-octanol/water:	No data available.		
Autoflammability°C:	No data available.	Vapour pressure:	0.31 kPa 20		
Relative density:	1.46	pH:	7		
VOC g/l:	No data available.				

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

PR229 WATERBORNE PRIMER

11.1. Information on toxicological effects

Hazardous ingredients:

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

ZINC OXIDE

IPR	RAT	LD50	240	mg/kg
ORL	MUS	LD50	7950	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

.P-PR229 WATERBORNE PRIMER

		Page: 6
Section 14: Transport informat	ion	
14.1. UN number		
	Not Regulated	
14.2. UN proper shipping name		
14.3. Transport hazard class(es	3)	
14.4. Packing group		
14.5. Environmental hazards		
Environmentally hazardous:	No Marine pollutant: No	
14.6. Special precautions for us	Ser	
Special precautions:	No special precautions.	
Section 15: Regulatory informa		
15.1. Safety, health and enviror	nmental regulations/legislation specific for the substance or mixture	
Specific regulations:	Not applicable.	
15.2. Chemical Safety Assessm	ient	
Section 16: Other information		
Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	453/2010.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	-	
	H312: Harmful in contact with skin.	
	H315: Causes skin irritation.	
	H319: Causes serious eye irritation.	
	H332: Harmful if inhaled.	
	H410: Very toxic to aquatic life with long lasting effects.	
	H412: Harmful to aquatic life with long lasting effects.	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive	
	and shall be used only as a guide. This company shall not be held liable for any	
	damage resulting from handling or from contact with the above product.	