

## SV103 ETCH/EPOXY THINNER

Compilation date: 05/05/2015

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** SV103 ETCH/EPOXY THINNER

**Product code:** SV103

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

**Tel:** 01753 584500

**Fax:** 01753 584501

**Email:** sales@unovaproducts.com

#### 1.4. Emergency telephone number

**Emergency tel:** 01753 584500

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; Eye Irrit. 2: H319; Acute Tox. 4: H332; Eye Dam. 1: H318; Asp. Tox. 1: H304; -: EUH044

**Most important adverse effects:** Flammable liquid and vapour. Harmful if inhaled. Causes skin irritation. Causes serious eye damage. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Risk of explosion if heated under confinement.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.

H332: Harmful if inhaled.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

EUH044: Risk of explosion if heated under confinement.

**Signal words:** Danger

# SAFETY DATA SHEET

## SV103 ETCH/EPOXY THINNER

Page: 2

**Hazard pictograms:** GHS02: Flame  
GHS05: Corrosion  
GHS07: Exclamation mark  
GHS09: Environmental



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+312: IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell.  
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### XYLENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	70-90%

##### BUTAN-1-OL

200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	10-30%
-----------	---------	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

**SAFETY DATA SHEET**  
SV103 ETCH/EPOXY THINNER

Page: 3

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

[cont...]

**SAFETY DATA SHEET**  
.P-SV103 ETCH/EPOXY THINNER

Page: 4

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**7.3. Specific end use(s)**

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**XYLENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-

**BUTAN-1-OL**

UK	-	154 mg/m <sup>3</sup>	-	-
----	---	-----------------------	---	---

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** Moderate

**Oxidising:** No data available.

**Solubility in water:** Insoluble

**Viscosity:** Non-viscous

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** 1

**Flash point°C:** 27

**Autoflammability°C:** 465-525

**Relative density:** 0.86

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** 7

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

[cont...]

**SAFETY DATA SHEET**  
.P-SV103 ETCH/EPOXY THINNER

Page: 5

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

**BUTAN-1-OL**

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

**Relevant hazards for substance:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 1)	-	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

[cont...]

# SAFETY DATA SHEET

.P-SV103 ETCH/EPOXY THINNER

Page: 6

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** 3

[cont...]

**SAFETY DATA SHEET**  
.P-SV103 ETCH/EPOXY THINNER

Page: 7

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Tunnel code:** D/E

**Transport category:** 1

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH044: Risk of explosion if heated under confinement.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.