

# SV107 PREMIUM CELLULOSE THINNER

Compilation date: 15/05/2015

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** SV107 PREMIUM CELLULOSE THINNER

**Product code:** SV107

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Unova Limited  
Unit 4 Transcentral  
Bennet Road  
Reading  
RG2 0QX  
Great Britain  
**Tel:** 01753 584500  
**Fax:** 01753 584501  
**Email:** sales@unovaproducts.com

### 1.4. Emergency telephone number

**Emergency tel:** 01753 584500

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Asp. Tox. 1: H304; Eye Dam. 1: H318; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE2: H373; STOT SE 3: H336

**Most important adverse effects:** May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

**Signal words:** Danger

**Hazard pictograms:** GHS05: Corrosion

**SAFETY DATA SHEET**  
SV107 PREMIUM CELLULOSE THINNER

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard



**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**2.3. Other hazards**

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous ingredients:**

ACETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---	---	--------

TOLUENE

203-625-9	108-88-3	-	Flam. Liq. 2: H225; Repr. 2: H361d; Asp. Tox. 1: H304; STOT RE 2: H373; Skin Irrit. 2: H315; STOT SE 3: H336	10-30%
-----------	----------	---	--	--------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%
-----------	-----------	---	--	--------

BUTAN-1-OL

200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

[cont...]

**SAFETY DATA SHEET**  
SV107 PREMIUM CELLULOSE THINNER

Page: 3

ISOBUTANOL

201-148-0	78-83-1	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	1-10%
-----------	----------	---	--	-------

ETHANOL

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	--	--------------------	-------

ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	--	-------

PROPAN-2-OL

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	<1%
-----------	---------	---	---	-----

METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%
-----------	---------	---	---	-----

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

**SAFETY DATA SHEET**  
SV107 PREMIUM CELLULOSE THINNER

Page: 4

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

[cont...]

# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 5

## 8.1. Control parameters

### Hazardous ingredients:

#### ACETONE

##### Workplace exposure limits:

##### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-

#### N-BUTYL ACETATE

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### TOLUENE

UK	191 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### XYLENE

UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### BUTAN-1-OL

UK	-	154 mg/m <sup>3</sup>	-	-
----	---	-----------------------	---	---

#### ISOBUTANOL

UK	154 mg/m <sup>3</sup>	231 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### 4-METHYLPENTAN-2-ONE

UK	208 mg/m <sup>3</sup>	416 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### ETHANOL

UK	1920 mg/m <sup>3</sup>	-	-	-
----	------------------------	---	---	---

#### ETHYL METHYL KETONE

UK	600 mg/m <sup>3</sup>	899 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### PROPAN-2-OL

UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-
----	-----------------------	------------------------	---	---

#### METHANOL

UK	266 mg/m <sup>3</sup>	333 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## DNEL/PNEC Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

[cont...]

# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 6

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** Moderate

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** No data available.

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

**Relative density:** No data available.

**pH:** No data available.

**VOC g/l:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

[cont...]

# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 7

## 11.1. Information on toxicological effects

### Hazardous ingredients:

#### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

#### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### TOLUENE

IVN	RAT	LD50	1960	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	6900	mg/kg

#### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

#### BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

#### ISOBUTANOL

IVN	MUS	LD50	417	mg/kg
IVN	RAT	LD50	340	mg/kg
ORL	RAT	LD50	2460	mg/kg

#### 4-METHYLPENTAN-2-ONE

IPR	RAT	LD50	400	mg/kg
ORL	MUS	LD50	1900	mg/kg
ORL	RAT	LD50	2080	mg/kg

[cont...]

# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 8

## ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

## PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

## METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

[cont...]



# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 9

## Hazardous ingredients:

### ACETONE

BLUEGILL ( <i>Lepomis macrochirus</i> )	LC50	8300	mg/l
---	------	------	------

## 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

## 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT or PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** 2

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

[cont...]

# SAFETY DATA SHEET

.P-SV107 PREMIUM CELLULOSE THINNER

Page: 10

Transport category: 1

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.