

## TC266 2PK POLYACRYLIC HIGH ADHESION

Compilation date: 28/04/2015

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** TC266 2PK POLYACRYLIC HIGHADHESION

**Product code:** TC266

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Unova Limited

Unit 4 Transcentral

Bennet Road

Reading

RG2 0QX

Great Britain

**Tel:** 01753 584500

**Fax:** 01753 584501

**Email:** sales@unovaproducts.com

#### 1.4. Emergency telephone number

**Emergency tel:** 01753 584500

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Flam. Liq. 2: H225; Carc. 1B: H350; Muta. 1B: H340; Skin Irrit. 2: H315; -: EUH208

**Most important adverse effects:** Contains 2-butanone oxime. May produce an allergic reaction. Highly flammable liquid and vapour. Causes skin irritation. May cause genetic defects. May cause cancer.

#### 2.2. Label elements

##### Label elements:

**Hazard statements:** EUH208: Contains 2-butanone oxime. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H340: May cause genetic defects.

H350: May cause cancer.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 2

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P308+313: IF exposed or concerned: Get medical attention.

## 2.3. Other hazards

**Other hazards:** Danger of serious damage to health by prolonged exposure.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### XYLENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%

##### 2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	10-30%
-----------	----------	--	--------------------	--------

##### N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

##### LIGHT OIL EXTRACT RESIDUES, HIGH BOILING - SOLVENT NAPHTHA (COAL)

266-013-0	65996-79-4	-	Carc. 1B: H350; Muta. 1B: H340	1-10%
-----------	------------	---	--------------------------------	-------

##### ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	---	-------

##### HYDROCARBONS, C9, AROMATICS

918-668-5	-	-	Flam. Liq. 3: H226; STOT SE 3: H335; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; STOT SE 3: H336	1-10%
-----------	---	---	--	-------

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 3

## DIBUTILSTAGNO DILAURATO (A)

201-039-8	77-58-7	-	Acute Tox. 3: H301; Acute Tox. 4: H312; Acute Tox. 4: H332	<1%
-----------	---------	---	---	-----

## 2-BUTANONE OXIME

202-496-6	96-29-7	-	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
-----------	---------	---	--	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Consult a doctor. Do not induce vomiting. If conscious, give half a litre of water to drink immediately.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** There may be mild irritation at the site of contact.
- Eye contact:** There may be irritation and redness.
- Ingestion:** There may be irritation of the throat.
- Inhalation:** No symptoms.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water spray.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes. Highly flammable. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 4

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Evacuate the area immediately.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**XYLENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-

**2-METHOXY-1-METHYLETHYL ACETATE**

UK	274 mg/m <sup>3</sup>	548 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**N-BUTYL ACETATE**

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**ETHYL METHYL KETONE**

UK	600 mg/m <sup>3</sup>	899 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 5

## DNEL/PNEC Values

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** esters

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Partially Soluble

**Viscosity:** Viscous

**Boiling point/range°C:** 125

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** 22

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** 460

**Vapour pressure:** No data available.

**Relative density:** No data available.

**pH:** No data available.

**VOC g/l:** 432

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 6

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

##### 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

##### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

##### 2-BUTANONE OXIME

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Germ cell mutagenicity	--	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 7

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** 3

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

[cont...]

# SAFETY DATA SHEET

TC266 2PK POLYACRYLIC HIGH ADHESION

Page: 8

## 14.6. Special precautions for user

**Special precautions:** No special precautions.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H301: Toxic if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.