

## PRODUCT DATA SHEET

## **AC147 – ANTICORROSIVE PAINT**

Compilation date: 06//11/2015

Revision No: 1

| DESCRIPTION     | Single component quick drying anticorrosive paint based on a modified alkyd resin   |                                    |                                 |             |
|-----------------|---|------------------------------------|---------------------------------|-------------|
| USES & BENEFITS | <ul> <li>For use on wrought iron, metal framework, staging etc</li> <li>Apply direct to suitably prepared steel</li> <li>Primer / Finish coat in one</li> </ul>   |                                    |                                 |             |
|                 |   |                                    | <ul> <li>Fast drying</li> </ul> |             |
|                 |   |                                    | PHYSICAL PROPERTIES*            | VOC Content |
|                 | Solids % by Weight  | : 60.5                             |                                 |             |
| Flash Point     | : 26°C  |                                    |                                 |             |
| Mixing Ratio    | : n/a   |                                    |                                 |             |
| FINISH          | Matt  |                                    |                                 |             |
| COLOUR          | Limited   |                                    |                                 |             |
| COVERAGE        | Up to 10m²/Ltr  |                                    |                                 |             |
| PREPARATION     | Substrate to be clean, dry and free from grease, rust and mill scale – best results by  |                                    |                                 |             |
|                 | blast cleaning.   |                                    |                                 |             |
| APPLICATION     | Brush / Roller  | : Unthinned                        |                                 |             |
|                 | Conventional Spray  | : Thin 10-15%                      |                                 |             |
|                 | Ambient temperature   | : 5-30°C                           |                                 |             |
|                 | Surface temperature   | : >3°C above the dew point         |                                 |             |
|                 | Clean equipment with STD Thinner  |                                    |                                 |             |
| DRYING TIMES    | At 20°C   |                                    |                                 |             |
|                 | Touch dry   | : 20 Minutes                       |                                 |             |
|                 | Recoat  | : Before 4 hours or after 16 hours |                                 |             |
| THINNER         | SV100   |                                    |                                 |             |
| STORAGE         | Keep away from food and drink. Store in original container securely closed and at   |                                    |                                 |             |
|                 | room temperature (For full text refer to health & safety data sheet)  |                                    |                                 |             |
| HEALTH & SAFETY | Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately. |                                    |                                 |             |
| DISCLAIMER      | The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages.  * VOC and solids content may vary with colour.   |                                    |                                 |             |

For paint system recommendations specific to your job requirements please contact our technical department.