

ProETCH

Etch Primer

PROETCH - is an ultimate etch primer for direct adhesion onto many difficult substrates including alloy, stainless steel, zintec and galvanise. This leaves a super smooth non-porous finish that is suitable for any topcoat.

- Outstanding etching properties
- Excellent anti-corrosive properties
- Fast drying
- Super smooth finish
- Supplied with 2 nozzles

Suitable substrates

Bare steel, cured paintings, polyester substrates, aluminium and galvanised sheet metals

Application data



1-2 coats @ 10 - 20µm



10 - 15 minutes @ 20°C



3 Minutes



ProBUILD, ProPRIME, Pro2KPRIME

Application method



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.



ProETCH

Etch Primer

Technical data

Chemical base	Nitro Cellulose
VOC content	338 g/500ml
Coverage	1.25m ²
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

