

# PRO MATIC®

**GP500 - GREY PRIMER**

**REDP500 - RED OXIDE PRIMER**

**WP500 - WHITE PRIMER**

## Products Characteristics

- Excellent corrosion prevention
- Optimizes the gloss finish of the topcoat
- Fast drying with good spraying properties and good coverage
- Excellent adhesion of subsequent topcoat
- Excellent filling properties and easy to sand
- Will adhere to wood, metal, aluminium and many other substrates.



## Properties

Product Type		nitro combi
Coverage		1.56 - 2.19m <sup>2</sup> per 500ml
Drying times	Dust Free	5 - 10minutes
	Touch Dry	10 - 20 minutes
	Sand able	after 2 hours
	Overcoat able	after 2 hours

The drying time depends on temperature, humidity and the thickness of the applied coat.

## Surface Preparation

- De-rust, abrade and clean surfaces prior to coating
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label

### Head Office

Second Avenue, Chatham, Kent, ME4 5AU

t: +44 (0)1634 823900

f: +44 (0)1634 813807

e: sales@alphacoatings.co.uk

### Irish Office:

Unit 45, Baldoye Ind Est, Baldoye  
Dublin 13, Ireland

t: +353 (0)1 8396511

f: +353 (0)1 8396098

e: ben@alphacoatings.co.uk