



### AQUAGRIP - WB HIGH ADHESION

Compilation date: 23/06/2015

Revision No: 1

<b>DESCRIPTION</b>	<b>AQUAGRIP</b> is a single pack high adhesion one coat enamel based on acrylic resins	
<b>USES &amp; BENEFITS</b>	Very Low VOC Long Life Anti-Bacterial Excellent adhesion EN71-3 Compliant FIRA BS6250	- Environmentally Friendly - Low Maintenance - Universal Hygiene Coating - Sticks To Most Surfaces - Non Toxic - High Scratch Resistance
<b>PHYSICAL PROPERTIES*</b>	Viscosity (DIN 4 at 20%) VOC Content Solids Content % by Weight	: 130 ± 10 : 65g/ltr – may vary depending on colour : Clear 32 ± 2 : Pigmented 42 ± 2
<b>FINISH</b>	Semi-Gloss Eggshell Matt	
<b>COLOUR</b>	Unlimited	
<b>COVERAGE</b>	8-10 m <sup>2</sup> /Ltr	
<b>PREPARATION</b>	Thoroughly abrade the substrate with red hand pads and degrease using <b>GREENCLEAN TM</b>	
<b>APPLICATION</b>	Brush Roller Spray - Conventional, airmix, airless, electrostatic, pressure fed spray systems (Ensure equipment is suitable for waterborne products) Ambient temperature Surface temperature Clean equipment with Distilled Water (tap water can be used but may not be as effective) or PT212 WB Equipment cleaner.	: Ready to use : Ready to use : Thin up to 5% : 15-30°C : >3°C above the dew point
<b>DRYING TIMES</b>	At 20°C Dust Free Touch dry Hard dry Recoat ** With Relative Humidity at no more that 65% and a good air flow	: 10 Minutes : 20 Minutes : 5 Hours : 2 hours
<b>THINNER</b>	Distilled Water (Tap water can be used if necessary but may affect the finish and drying times)	
<b>STORAGE</b>	Store in original container securely closed and in a dry, well-ventilated area away from sources of heat and ignition. (For full text refer to health & safety data sheet). <b>PROTECT FROM FREEZING.</b>	
<b>HEALTH &amp; SAFETY</b>	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.	
<b>DISCLAIMER</b>	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages. * VOC and solids content may vary with colour.	

*For paint system recommendations specific to your job requirements please contact our technical department.*

**THAMES COATINGS**

| Sutton Lane, Langley, SL3 8AR | T: 01753 584500 | F: 01753 584501 | E: sales@thamescoatings.com |