Technical Data Jotun Thinner No. 7



Product description

Solvent thinner.

Recommended use

General purpose thinner for acrylic and chlorinated rubber paints and antifouling compositions.

Consult the technical data sheet for the actual Jotun product.

Physical properties

ColourClearSolids (vol %)* 0 ± 0

Flash point 25°C ± 2 (Setaflash)

VOC 7,26 lbs/gal (871 gms/ltr) USA-EPA Method 24

870 gms/ltr ÙK-PG6/23(97). Appendix 3

*Measured according to ISO 3233:1998 (E)

Storage

The product must be stored below 25°C and in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care.

Packing size

5 litre container or 20 litre container.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

Jotun Thinner No. 7 Page 1 of 2

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 6 DECEMBER 2007 BY JOTUN THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED

Jotun Thinner No. 7 Page 2 of 2