

PT116 – DEGREASER

Compilation date: 10/09/2015

Revision No: 1

DESCRIPTION	A powerful industrial degreaser for cleaning and degreasing
USES & BENEFITS	<ul style="list-style-type: none"> • Quickly cuts grime and degreases metal • Ideal for use prior to painting • Allow paint to adhere better to the substrate • Reduces chances of paint fish eyeing
COLOUR	Clear
APPLICATION	Lint Free Cloth/Rag : : Wipe on, Wipe off (with dry cloth) Ambient temperature : 5-30°C Surface temperature : >3°C above the dew point Clean equipment with STD Thinner
STORAGE	Store in original container securely closed and in a cool, dry, well ventilated place away from sources of ignition (For full text refer to health & safety data sheet)
HEALTH & SAFETY	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.
DISCLAIMER	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages.

For paint system recommendations specific to your job requirements please contact our technical department.