

PT120 – ALKALINE CLEANER

Compilation date: 18/09/2015
Revision No: 1

DESCRIPTION	Fast acting alkaline cleaner with powerful grease cutting properties
USES & BENEFITS	<ul style="list-style-type: none"> • Fast removal of dirt, grease, oil and other contaminants prior to painting • Ideal for floors and exterior cladding • High concentrate formula for cost effective usage
PHYSICAL PROPERTIES*	Flash Point : >70°C Mixing Ratio : see application instructions.
COVERAGE	Depends on level of contamination and cleaning required.
APPLICATION	<p>Dilute with water before use : 1:100 for light cleaning : 1:20 for heavily soiled areas</p> <p>Apply liberally and scrub surface to loosen stubborn dirt. Rinse clean with water. Repeat process as necessary until surface is clean.</p>
DRYING TIMES	Allow substrate to fully dry before over coating with subsequent paint systems.
THINNER	Water
STORAGE	Store in original container securely closed and in a dry, well ventilated area away from sources of heat and ignition. (For full text refer to health & safety data sheet)
HEALTH & SAFETY	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.
DISCLAIMER	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages.

For paint system recommendations specific to your job requirements please contact our technical department.