

PT220 – PAINT & VARNISH REMOVER

Compilation date: 18/09/2015

Revision No: 1

DESCRIPTION	A traditional 'Gel' type varnish and paint stripper that effectively removes a wide range of interior and exterior oil, water and solvent based lacquers, varnishes and paints.
USES & BENEFITS	<ul style="list-style-type: none"> • Ideal for prepping back to the original substrate • Fast working Industrial grade • Removes most paints including 2 packs • Gel consistency ideal for vertical or awkward areas.
COVERAGE	Depends on level of contamination and thickness of paint that's being removed.
PREPARATION	Soak up and remove any existing wet paint/varnish. Light scoring of the coated surface may enhance performance, however do not sand if any coats contain lead.
APPLICATION	<p>Our paint & varnish remover contains corrosive substances and should only be used in a well ventilated area with protective clothing such as gloves and safety glasses or goggles.</p> <p>When stripping painted surfaces, paint a thick coat of wood stripper onto about a square meter at a time and leave for between 5 and 10 minutes before removing the gel. Removal of the gel can be done with a scraper or with steel wool. If using steel wool then a good pair of gloves should be worn as strippers always contain aggressive stripping chemicals.</p> <p>If some layers remain on the surface then the process can be repeated as many times as is necessary. Once you feel that you are virtually back to the bare wood then the surface should be washed with neat solvent. The one you use depends on the type of paint or varnish being removed.</p>
THINNER	N/A
STORAGE	Keep away from food and drink. Store in original container securely closed and at room temperature (For full text refer to health & safety data sheet)
HEALTH & SAFETY	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.
DISCLAIMER	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages.

For paint system recommendations specific to your job requirements please contact our technical department.