

SCX1 - Stonechip Coatings

Product Characteristics

- Stonechip is a repaintable plastic protective, single component.
- Sound-deadening and anti-abrasive characteristics.
- Ideal for repairing underdoor and sidebands, wheel arches and underbody.
- Does not contain lead, tar, asbestos or chlorinated hydrocarbons.

Properties

Product Type	Alkyd Resin
Colour	Black—Grey—White
Drying times	Dust free 15-20minutes Overcoating 2-3 hours

Surface Preparation

- Thoroughly clean and degrease old paint surfaces with a suitable spirit wipe or thinner.
- Wet flat with 400 grade paper. For bare metal use 180 grade paper
- Re-clean and dry

VOC DATA: 2004/42/IIB(e)(840)830 The EU limit value for this product (product category: IIB.e) in ready to use form is max 840 g/litre of VOC. The VOC content of this product in ready to use form is max 830g/l



Head Office
Second Avenue, Chatham, Kent, ME4 5AU
t: +44 (0)1634 823900
f: +44 (0)1634 813807
e: sales@alphacoatings.co.uk

Irish Office:
Unit 45, Baldoye Ind Est, Baldoye
Dublin 13, Ireland
t: +353 (0)1 8396511
f: +353 (0)1 8396098
e: ben@alphacoatings.co.uk