

SL195 – BLACK BITUMEN PAINT

DESCRIPTION	Single component high performance solvent borne bituminous black paint
USES & BENEFITS	<ul style="list-style-type: none"> * Waterproof coating for steel and concrete. * Excellent rejuvenation of boat hulls above and below the waterline * Fast application – supplied ready for use * Conforms to BS3416:Type 1 Class A
PHYSICAL PROPERTIES*	VOC Content Solids % by Weight : Flash Point : 38°C Mixing Ratio : n/a
FINISH	Gloss
COLOUR	Black
COVERAGE	Up to 8m ² /Ltr
PREPARATION	All surfaces to be clean, dry and free from loose or flaking material, dust and grease. Areas of rust should be thoroughly wire brushed and treated with RC140.
APPLICATION	Brush, Roller or Airless Spray – Apply unthinned. Apply at least 2 coats allowing each coat to dry in between. Ambient temperature 5-30°C Surface at least 3°C above the dew point Clean equipment with STD Thinner
DRYING TIMES	At 20°C Approx 6 hours
THINNER	SV104
STORAGE	Containers must be kept sealed and stored undercover away from sources of heat and ignition.
	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.
DISCLAIMER	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages. * VOC and solids content may vary with colour.

For paint system recommendations specific to your job requirements please contact our technical department.

THAMES COATINGS

| Sutton Lane, Langley, SL3 8AR | T: 01753 584500 | F: 01753 584501 | E: office@thamescoatings.co.uk |