

WB153 – WATERBASED TOPCOAT

Compilation date: 07/09/2015

Revision No: 1

DESCRIPTION	Single component waterborne environmentally friendly topcoat
USES & BENEFITS	<ul style="list-style-type: none"> • General purpose waterborne topcoat for suitably primed interior surfaces • Ultra-smooth finish • Low odour & fast drying
PHYSICAL PROPERTIES*	VOC Content : Solids % by Weight : 32 Flash Point : n/a Mixing Ratio : n/a
FINISH	Semi-Gloss Eggshell Matt
COLOUR	Unlimited
COVERAGE	Up to 8-10m ² /Ltr
PREPARATION	Substrate to be primed, clean & dry
APPLICATION	Conventional Spray : Thin <5% Pressure Fed : Thin <5% Ambient temperature : 15-30°C Surface temperature : >3°C above the dew point Clean equipment with Water or PT212
DRYING TIMES	At 20°C (RH<65% with good air movement) Touch dry : 30 minutes Hard dry : 4 hours
THINNER	SV109
STORAGE	Store in original container securely closed and in a dry, well ventilated area away from sources of heat and ignition. (For full text refer to health & safety data sheet). PROTECT FROM FREEZING.
HEALTH & SAFETY	Refer to Health & Safety Data Sheet before using this product. Please observe the precautionary notices displayed on the container. Spray application (if appropriate) should be done under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleaner, soap and water. Eyes should be well flushed with fresh clean water and medical attention sought immediately.
DISCLAIMER	The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. User will be deemed to have satisfied themselves independently as to the suitability of this product for their own particular purpose. In no event shall Thames Coatings be liable for consequential or incidental damages. * VOC and solids content may vary with colour.

For paint system recommendations specific to your job requirements please contact our technical department.

THAMES COATINGS

| Sutton Lane, Langley, SL3 8AR | T: 01753 584500 | F: 01753 584501 | E: sales@thamescoatings.com |